




Product: [10GX KEYCONNECT JACKS](#)



10GX Modular Jack, Category 6A, RJ45, KeyConnect Style

Product Description

CAT6A KeyConnect Jacks are available in several colors.

Technical Specifications

Product Overview

| | |
|------------------------|--|
| Suitable Applications: | IBDN System 10GX, TIA Category 6A, ISO Class EA, 10GBASE-T |
|------------------------|--|

Physical Characteristics (Overall)

| | |
|----------------|--|
| Height: | 0.9 in |
| Width: | 0.675 in |
| Depth: | 1.17 in |
| Wiring Scheme: | T568A/B |
| Packaging: | Individually packaged in a plastic bag. Standard pack of 50 units. |
| Weight: | 0.016 lbs |

Connectors

Materials

| Description | Material | Type |
|------------------|--|--------------|
| Front Connection | Flexible PCB with 50 μ inch Gold over Nickel | Flexible PCB |
| Rear Connection | Phosphor Bronze with Tin Plating over Nickel | IDC |
| Connector Body | Plastic - UL94V-0 | |

Electrical Characteristics

| | |
|-------------------------|---------------------------------|
| Dielectric Strength: | 1,000V RMS @ 60 Hz for 1 minute |
| Current Rating: | 1.500 A |
| Insulation Resistance: | 500 M-Ohm Minimum |
| Max Contact Resistance: | 20 mOhm |
| Termination Resistance: | 2.5 mOhm |

Temperature Range

| | |
|---------------------------------|----------------|
| Installation Temperature Range: | -10°C to +60°C |
| Storage Temperature Range: | -40°C to +70°C |
| Operating Temperature Range: | -10°C to +60°C |

Mechanical Characteristics

| | |
|--|----------------------------|
| Footprint/Type: | KeyConnect |
| Tool Compatibility: | Belden 110 Connecting Tool |
| Plug /Jack Compatibility: | RJ45, RJ11 |
| Termination Front Connection: | Mated Connection |
| Termination Front Connection Durability: | 750 cycles |
| Termination Rear Connection: | IDC Connection |

| | |
|---|-----------------|
| Termination Rear Connection Durability: | 20 terminations |
| Cable/Connector Retention: | 15 lbs. |
| Connector/Hardware Retention: | 20 lbs |
| Plug/Connector Retention: | 11.250 lbs |

Standards

| | |
|---------------------------------------|---|
| Data Category: | Category 6A |
| TIA/EIA Compliance: | Category 6A - TIA 568.2-D, ISO/IEC 11801:2002 Amendment 2 |
| Other Standards: | FCC Part 68, Subpart F, IEC 60603-7 |
| Third Party Performance Verification: | ETL - Verified Category 6A |

Applicable Environmental and Other Programs

| | |
|---------------------------------|--------|
| Environmental Space: | Indoor |
| EU Directive 2002/95/EC (RoHS): | Yes |
| MII Order #39 (China RoHS): | EUP 50 |

Flammability, LS0H, Toxicity Testing

| | |
|-----------------|---------------------|
| Safety Listing: | ACA, c(UL)us Listed |
|-----------------|---------------------|

Related Part Numbers

| | |
|----------------|---|
| Related Parts: | Compatible with KeyConnect Faceplates, Adapters, Boxes and Patch Panels |
|----------------|---|

Variants

| Item # | Color | Packaging |
|----------|-----------------|--|
| AX102281 | Almond | Single Pack |
| AX102283 | Black | Single Pack |
| AX104156 | Blue | Single Pack |
| AX104158 | Brown | Single Pack |
| AX102282 | Electric White | Single Pack |
| AX102280 | Gray | Single Pack |
| AX104155 | Green | Single Pack |
| AX103073 | Ivory | Single Pack |
| AX104152 | Orange | Single Pack |
| AX104157 | Purple | Single Pack |
| AX104232 | Stainless Steel | Individually packaged in a plastic bag. Standard pack of 50 units. |
| AX104233 | Stainless Steel | Individually packaged in a plastic bag. Standard pack of 50 units. |
| AX102288 | TIA Blue | Single Pack |
| AX102290 | TIA Brown | Single Pack |
| AX102287 | TIA Green | Single Pack |
| AX102284 | TIA Orange | Single Pack |
| AX102289 | TIA Purple | Single Pack |
| AX102285 | TIA Red | Single Pack |
| AX102286 | TIA Yellow | Single Pack |
| AX104154 | Yellow | Single Pack |

Product Notes

| | |
|-----------------|--|
| Included Parts: | 1 X-Bar |
| Notes: | Please see Installation Guide PX103771 |

History

| | |
|----------------------|--|
| Update and Revision: | Revision Number: 0.304 Revision Date: 05-10-2023 |
|----------------------|--|

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.