HD CCTV TESTER

4300BA

4300BA HD CCTV tester is for maintenance and installation of HD Analogue camera, Support AHD, TVI and CVI video signal, quickly check the camera problem and installation process. 4300BA Adopted with lithium battery, video and audio input, seven kinds of standard color bar output terminal, DCI2V power suppy output ebables user to inpect, adjust camera or confirm installation. The palm-sized design makes it convenient during the installation or maintenance process.

Key Features

- Portable tester with 4.3-inch TFT display
- Automatically recognize NTSC/PAL video
- Home network cable test function
- Power saving mode can display in atanby state
- Small form factory convenient for work process
- Support DCI2V / IOOmA



Accessories



Video, audio input and power output socket



Network cable test adapter



Wrist Strap

Monitor

4.3" high image resolution monitor enables to show clear image that fits any place use.

Long Working Time

Equips with high capacity Lithium battery. Each 6 hours recharge lasting up to 4 - 6 working hours.

Humanized Design of Appearance

Hand-hold design for professionals. Easy operation without taking off the gloves, speeds your works.

Support DC Power for Camera

Convenient for check camera condition and adjust direction of camera, makes the installation and reparing more easier.

Specifications

Display	4.3" TFT Color LCD
Number of Pixel	480RGB(H) x 272(V)
Video In	Video In x I (BNC connector)
Export	7 kinds of color bar signal output
	DC power output xl (Support CCD camera power source / Max electric currency I500mA
System Format	AHD, TVI, CVI, CVBS (NTSC/PAL)
Light Instruction	2 LEDs (power IND = Green / charging IND = Red)
Battery Specification	Rechargeable Lithium battery: 3.7V 4200mAh
Power Supply	External power: DC5V 2.0A adapter
Dimension/Weight	178mm(L) x II0mm(W) x 40mm(H) / 350g