



# HRX-435

4CH Pentabrid DVR



## Key Features

- 5-in-1 4CH Pentabrid DVR
- AHD/HDTVI/HDCVI/CVBS/IP inputs
- Total 6CH (Analog Max. 4CH and Network Max. 6CH supported), up to 8MP
- H.265, H.264, MJPEG codec
- 8/8fps@8MP, 12/12fps@5MP recording
- Coaxial control
- Up to 2 SATA HDDs(6TB/HDD)
- HDMI/VGA Dual monitor
- P2P service (QR code connect)

# HRX-435

4CH Pentabrid DVR

## Specifications

### Display

Analog camera	<b>Inputs</b>	4CH(1Vp-p 75ohm, BNC)
	<b>Signal Type</b>	AHD(8MP, 5MP, 4MP, 1080p, 720p) HDTVI(8MP, 5MP, 4MP, 1080p, 720p) HDCVI(5MP, 4MP, 1080p, 720p) CVBS(NTSC/PAL)
Network camera	<b>Inputs</b>	Max. 6CH
	<b>Resolution</b>	8MP ~ CIF
	<b>Protocols</b>	SUNAPI(Wisenet), ONVIF
Live	<b>Local Display</b>	1x HDMI, 1x VGA (simultaneous output) HDMI: 3840 x 2160, 2560x1440, 1920x1080, 1280x1024, 1280x720 VGA: 1920x1080, 1280x1024, 1280x720
	<b>Resolution</b>	[Analog Camera(NTSC/PAL)] - 8MP(15/12fps), 5MP(20/12fps), 4MP(30/25fps), 2MP(30/25fps), 1MP(30/25fps), 960H(or 720H)(30/25fps) * per CH [Network Camera] - Typ. 2MP(120fps)

### Performance

Record	<b>Compression</b>	H.265, H.264, MJPEG
	<b>Record Rate(Analog)</b>	Analog Camera (Main Stream) 8MP 8/8fps, 5M 12/12fps, 4M 15/12fps, 2M 30/25fps, 720p 30/25fps, 960H/640H 30/25fps (NTSC/PAL per CH) (Sub Stream) 720p or higher : 640x368 full fps/CH, SD signal : upto CIF full fps/CH * The maximum recording frame rate depends on the frame rate of the input camera.
	<b>Recording Bandwidth</b>	Max. 30Mbps
	<b>Resolution</b>	8MP ~ CIF
	<b>Mode</b>	Manual, Schedule (Continuous/Event), Event(Pre/Post), Dual Track
	<b>Event Trigger</b>	Alarm Input Analog Camera : Video Loss, Motion Detection, Tampering Network Camera : Camera Event (Sensor, MD, Video analytics), VA event (Tampering, Enter / Exit, Passing, Virtual- line, (Dis)Appear, Face Detection, Audio detection), Defocus camera event, Dynamic camera event
Search & Play	<b>Event Action</b>	E-mail, PTZ preset, Alarm out, Buzzer, Monitor out
	<b>Playback Bandwidth</b>	Max. 32Mbps (6CH simultaneously)
	<b>User</b>	Max. 4 Users (Local 1, Remote 3)
	<b>Simultaneous playback</b>	6CH(Local Monitor), 4CH(CMS, Wisenet Mobile) 1CH(Web)
Storage	<b>Fisheye Dewarping</b>	WEB / CMS
	<b>Supported HDD</b>	Up to 6TB
Backup	<b>HDD Slot</b>	SATA 2ea(Max 12TB)
	<b>File backup</b>	BU, EXE(Include Player), AVI(Webviewer only)
	<b>Function</b>	Max. 6 CH play, Date-time/title display

### Functions

PTZ	<b>Control</b>	Via GUI, Webviewer, SSM, SmartViewer, Wisenet Mobile Viewer, System Controller
Smart phone	<b>Support Model</b>	iOS, Android
	<b>Protocol Support</b>	RTP, RTSP, HTTP, CGI(SUNAPI)
	<b>Control</b>	Live(4ch) : Multi-Profile Support Playback(4Ch Multi Playback, Max 2MP) Event push
	<b>Max. Remote Users</b>	Search(3), Live Unicast(10)
Redundancy	<b>ARB</b>	Support
Easy configuration		Setup Wizard (Language Date/Time, Password, Network, Auto Camera Configuration), P2P (QR code)

<b>Coaxial Control</b>	CVBS(Pelco-C)/AHD/CVI/TVI	
<b>Interface</b>		
<b>HDMI</b>	1EA	
<b>VGA</b>	1EA	
<b>BNC</b>	4CH In / 1CH Out(Spot Output)	
<b>Audio</b>	Out(1EA, RCA, Line)	
<b>Ethernet</b>	RJ-45(10/100 BASE-T)	
<b>Alarm</b>	In 4EA, Out 2EA - Relay Out1(NO/NC/COM) - Relay Out2(NO/COM)	
<b>USB</b>	2EA(Front USB2.0)	
<b>Serial(Protocols)</b>	RS-485/422 (Samsung-T/Pelco-D/Pelco-p) * for PTZ	
<b>Power inlet</b>	1EA DC Input Jack	
<b>System</b>		
<b>System Control</b>	Mouse, Webviewer, System Controller(SPC-7000, SPC-6000, SPC-2000)	
<b>Language</b>	English, French, German, Italian, Spanish, Russian, Turkish, Polish, Dutch, Swedish, Czech, Portuguese, Danish, Rumanian, Serbian, Croatian, Hungarian, Greek, Norwegian, Finnish, Korean, Chinese, Japanese, Thai	
<b>Environmental</b>		
<b>Operating Temperature</b>	0°C to +40°C(+32°F to +104°F)	
<b>Operating Humidity</b>	20% ~ 85% RH	
<b>Certification</b>	UL, CE, FCC, KC	
<b>Electrical</b>		
<b>Power Input</b>	DC12V	
<b>Power Consumption</b>	Max. 40W (6T HDD 2ea)	
<b>Mechanical</b>		
<b>Color / Material</b>	Black / Metal	
<b>Dimension (WxHxD)</b>	370.0x 44.0 x 320mm(14.57" x 1.73" x 12.6")	
<b>Weight</b>	Approx. 2.3Kg (5.07 lb, 4TB HDD 1ea) TBD	
<b>Network</b>		
<b>Protocol</b>	TCP/IP, UDP/IP, RTP (UDP), RTP (TCP), RTSP, NTP, HTTP, DHCP (Server, Client), PPPoE, SMTP, ICMP, IGMP, ARP, DNS, DDNS, uPnP, HTTPS, SNMP, ONVIF (Profile-S), SUNAPI(Server, Client)	
<b>DDNS</b>	Wisenet DDNS	
<b>Transmission speed</b>	Analog Camera) (Main Stream) 8MP 8/8fps, 5M 12/12fps, 4M 15/12fps, 2M 30/25fps, 720p 30/25fps, 960H/640H 30/25fps (NTSC/PAL per CH) (Sub Stream) 720p or higher : 640x368 full fps/CH, SD signal : upto CIF full fps/CH * The maximum recording frame rate depends on the frame rate of the input camera.	
<b>Transmission Bandwidth</b>	Max. 32Mbps	
<b>Audio</b>	<b>Input/Output</b>	4 Line in / 1 Line out
	<b>Compression</b>	G.711 (N/W Cam G.711, 726)
	<b>Audio Communication</b>	2-Way
<b>Max Remote Users</b>	Search(3), Live Unicast(10), Multicast(20)	
<b>Security</b>	IP address filtering, User access log, 802.1x Authentication, Encryption (ID/PW, Recording, Transmission, Backup) Device Certificate(Hanwha Techwin Root CA)	
<b>Viewer Software</b>	SSM, Webviewer, Smart Viewer, Wisenet mobile Support SDK/CGI(SUNAPI) for integration to 3'rd party VMS	


# HRX-435

4CH Pentabrid DVR

CAD

Unit: mm [inch]

This parts should not contain any substances which are specified in A800-0032K



Appearance drawing HRX-435  
Unit : mm[inches]