



# SMT-2431

24" LED Monitor



## Key Features

- Frameless Design
- Support up to 1920 x 1080 resolution
- Brightness : 250cd/m<sup>2</sup>
- Contrast : 4000:1
- Viewing Angle(H/V) : 178°/178°
- Response Time : 14ms
- Video Input : HDMI, VGA
- Panel Life : 30,000 hours

# SMT-2431

24" LED Monitor



## Specifications

### Display

Type	LED Monitor
Screen Size	23.8"
Max. Resolution	1920*1080
Brightness	250cd/m <sup>2</sup>
Contrast Ratio	4000:1 (Typical)
Aspect Ratio	16:9
Viewing Angle (H/V)	178°/178°
Display Color	16.7M (6bit+FRC)
Response Time	14ms(Typical)
Panel Life	30,000 hours

### Interface

Video	Connectors	VGA(1) HDMI (1)
VGA	Connector	VGA
	Available Format	640 × 480@60Hz/72Hz/75Hz;720 × 400@70Hz ; 800 × 600@60Hz/72Hz/75Hz;1024 × 768@60Hz/75Hz;1280 × 1024@60Hz/75Hz;1440 × 900@60Hz;1680 × 1050@60Hz ; 1920 × 1080@60Hz
HDMI	Connector	HDMI
	Available Format	640 × 480@60Hz/72Hz/75Hz;720 × 400@70Hz ; 800 × 600@60Hz/72Hz/75Hz;1024 × 768@60Hz/75Hz;1280 × 1024@60Hz/75Hz;1440 × 900@60Hz;1680 × 1050@60Hz ; 1920 × 1080@60Hz

### On Screen Display

Functions	VESA™ DPM Compatible
Language	12 (English, French, German, Italian, Simplified Chinese, Traditional Chinese, Korean, Japanese, Espanola, Portuguese, Russian, Arabic )

### General

Electrical	Input Voltage	AC 100 ~ 240V(50/60Hz)
	Power Consumption	<30W
Environmental	Operating Temperature	0 ~ +40°C (+32°F ~ +104°F)
	Operating Humidity	10% ~ 80% (non-condensing)
Mechanical	Dimensions with Stand (WxHxD)	540*420.3*224.1mm
	Dimensions without Stand (WxHxD)	540*324*46mm
	Weight	3.5Kg
	Cabinet Color	Black
	VESA Mounts Interface	100*100mm

# SMT-2431

24" LED Monitor



CAD

Unit: mm [inch]

