



SMT-3234

32" LED Monitor



Key Features

- Support up to 1,920 x 1,080 resolution
- Contrast ratio 2250 :1 (Typ) , 2000:1 (Min)
- Fast response time 8ms
- Video input : HDMI, DVI, VGA, BNC
- Panel life 30,000 hours
- Weight : 5.6Kg

SMT-3234

32" LED Monitor



Specifications

Display

Type	LED
Screen Size	31.5"
Max. Resolution	1,920 x 1,080
Brightness	300cd/m ²
Contrast Ratio	2250 :1 (Typ) ,2000:1 (Min)
Aspect Ratio	16:9
Viewing Angle (H/V)	178°/178°
Display Color	16.7 million
Response Time	8ms(G to G)
Video System	NTSC/PAL
Panel Life	30,000 hours
Filter Type	3D combfilter

Interface

Video	Connectors	VGA, DVI, HDMI, BNC
Composite Video	Input	1 port, BNC
VGA	Connector	1port Analog D-sub(15 pin), 1 port DVI-D
	Available Format	640 x 480@60Hz/66Hz/72Hz/75Hz (VGA), 800 x 600@56Hz/60Hz/72Hz/75Hz (SVGA), 1,024 x 768@60Hz/70Hz/75Hz (XGA), 1,152 x 864@75Hz, 1,280 x 720@60Hz, 1,280 x 800@60Hz, 1,280 x 1,024@60Hz/75Hz (SXGA), 1,360 x 768@60Hz, 1,440 x 900@60Hz, 1,600 x 900@60Hz, 1,680 x 1,050@60Hz, 1,920 x 1,080@60Hz
HDMI	Connector	1 port HDMI
	Available Format	640 x 480p@60Hz, 720 x 480p@60Hz, 720 x 576p@50Hz, 1,280 x 720p@50Hz/60Hz, 1,920 x 1,080i@60Hz, 1,920 x 1,080p@60Hz
Audio	Connector	3.5mm Mini Phone Jack
	Output Signal	Loop-through line level(PC only), Speakers : 2 x 2Watt
Application Support		Remote Controller

On Screen Display

Functions	VESA™ DPM Compatible
Language	Chinese(Simplified), English, French, German, Spanish,Dutch,Russian,Arabic

General

Electrical	Input Voltage	AC 100 ~ 240V(50/60Hz)
	Power Consumption	<60W
Environmental	Operating Temperature	0 ~ +40°C (+32°F ~ +104°F)
	Operating Humidity	10% ~ 80% (non-condensing)
Mechanical	Dimensions without Stand (WxHxD)	728.8 x 433.1 x 51.4mm
	Weight	5.6kg
	Cabinet Color	Black
	VESA Mounts Interface	100 x 100mm

SMT-3234

32" LED Monitor



CAD

Unit: mm [inch]

