

XNV-6120

2M H.265 NW Dome Camera



Key Features

- Max. 2Megapixel (1920 x 1080) resolution
- 5.2 ~ 62.4mm (Optical 12X) Optical Lens
- Max. 60fps@all resolutions (H.265 / H.264)
- H.265, H.264, MJPEG Codec Supported, Multiple streaming
- Day & Night (ICR), WDR (150dB), Defog
- IVA, Fog Detection, Sound Classification, Tampering
- Motion Detection, Handover
- SD / SDHC / SDXC 2 Slot (Max. 512GB)
- Hallway View, WiseStreamII Support
- IP67 / IP66, NEMA 4X, IK10

Compatible Accessories (Optional)



SBP-300HM6



SHP-1680FW



SBP-160TM



SBV-158G



SHD-1600FPW



SPB-VAN71



SBV-160WC



SBP-390WM2



SBP-300WM



SBP-300WM1



SBP-300KM



SBP-300NB



SBP-300PM



SBP-300B

Video	
Imaging Device	1/2.8" 2MP CMOS
Resolution	1920x1080, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240
Max. Framerate	H.265/H.264: Max. 60fps/50fps(60Hz/50Hz) MJPEG: Max. 30fps/25fps(60Hz/50Hz)
Min. Illumination	Color: 0.03Lux(F1.6, 1/30sec) BW: 0.003Lux(F1.6, 1/30sec)
Video Out	CVBS: 1.0 Vp-p / 75Ω composite, 720x480(N), 720x576(P) for installation USB: Micro USB Type B, 1280x720 for installation
Lens	
Focal Length (Zoom Ratio)	5.2~62.4mm(12x) zoom
Max. Aperture Ratio	F1.6(Wide)~F3.0(Tele)
Angular Field of View	H: 54.58°(Wide)~5.30°(Tele) / V: 32.19°(Wide)~3.00°(Tele) / D: 61.4(Wide)~6.06(Tele)
Min. Object Distance	2.1m(6.89ft)
Focus Control	OneshotAF
Lens Type	DC auto iris
Pan / Tilt / Rotate	
Pan / Tilt / Rotate Range	0°~354° / 0°~75° / 0°~355°
Operational	
Camera Title	Displayed up to 85 characters
Day & Night	Auto(ICR)
Backlight Compensation	BLC, HLC, WDR, SSDR
Wide Dynamic Range	150dB
Digital Noise Reduction	SSNR V
Digital Image Stabilization	Support
Defog	Support
Motion Detection	8ea, 8point polygonal zones
Privacy Masking	32ea, polygonal zones - Color: Grey/Green/Red/Blue/Black/White - Mosaic
Gain Control	Low / Middle / High
White Balance	ATW / AWC / Manual / Indoor / Outdoor
LDC	Support
Electronic Shutter Speed	Minimum / Maximum / Anti flicker (2~1/12,000sec)
Video Rotation	Flip, Mirror, Hallway view(90°/270°)
Analytics	Defocus detection, Directional detection, Fog detection, Face detection, Motion detection, Digital auto tracking, Appear/Disappear, Enter/Exit, Loitering, Tampering, Virtual line, Audio detection, Sound classification
Alarm I/O	Input 1ea / Output 1ea
Alarm Triggers	Analytics, Network disconnect, Alarm input




Alarm Events	File upload via FTP and e-mail Notification via e-mail SD/SDHC/SDXC or NAS recording at event triggers Alarm output
Audio In	Selectable(mic in/line in) Supply voltage: 2.5VDC(4mA), Input impedance: 2K Ohm
Audio Out	Line out, Max.output level: 1Vrms
Network	
Ethernet	RJ-45(10/100BASE-T)
Video Compression	H.265/H.264: Main/Baseline/High, MJPEG
Audio Compression	G.711 u-law /G.726 Selectable G.726(ADPCM) 8KHz, G.711 8KHz G.726: 16Kbps, 24Kbps, 32Kbps, 40Kbps AAC-LC: 48Kbps at 16KHz
Smart Codec	Manual(5ea area), WiseStream II
Bitrate Control	H.264/H.265: CBR or VBR MJPEG: VBR
Streaming	Unicast(20 users) / Multicast Multiple streaming(Up to 10 profiles)
Protocol	IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour, LLDP, SRTSP
Security	HTTPS(SSL) Login Authentication Digest Login Authentication IP Address Filtering User access log 802.1X Authentication(EAP-TLS, EAP-LEAP)
Application Programming Interface	ONVIF Profile S/G/T SUNAPI(HTTP API) Wisenet open platform
General	
Web Viewer	Supported OS: Windows 7, 8.1, 10, Mac OS X 10.10, 10.11, 10.12 Recommended Browser: Google Chrome Supported Browser: MS Explore11, MS Edge, Mozilla Firefox(Window 64bit only), Apple Safari(Mac OS X only)
Edge Storage	Micro SD/SDHC/SDXC 2slot 512GB
Memory	1024MB RAM, 256MB Flash
Environmental & Electrical	
Operating Temperature / Humidity	-40°C~+55°C(-40°F ~ +131°F) / Less than 90% RH * Start up should be done at above -35°C
Storage Temperature / Humidity	-50°C ~ +60°C (-58°F ~ +140°F) / Less than 90% RH
Certification	IP66/IP67, IK10, NEMA 4X
Input Voltage	PoE(IEEE802.3af, Class3), 12VDC, 24VAC
Power Consumption	PoE : Max 8.2W 12VDC : Max. 7W 24VAC : Max. 8.2W

Mechanical

Color / Material	Ivory / Aluminum
Product Dimensions / Weight	Ø160x128.5mm(6.30"x5.06"), 985g(2.17 lb)

- The latest product information / specification can be found at hanwha-security.com
- Design and specifications are subject to change without notice.
- Wisenet is the proprietary brand of Hanwha Techwin, formerly known as Samsung Techwin.

NO	PART NAME	CODE NO.	MATERIAL	QTY	REMARK
1	ASSY-XNV-61208-Kentou-1st-161208	049661	MATERIAL	1	REMARK



CHANGE

STANDARD TOLERANCE					UNIT	mm	DESIGN	CHECK	APPROVAL	PART NAME	ASSY-XV-6120R-Kentou-1st-161208
DIV	1st	2nd	3rd	4th			M.Fujiwara	-	ByungMoon	Jun	
0-16	0.05	0.03	0.02	0.01	SCALE	1/1	17.03.24	-	17.03.24	MODEL NAME	
16-40	0.05	0.03	0.02	0.01							
40-100	0.1	0.05	0.03	0.02							
100-200	0.1	0.05	0.03	0.02							
200-500	0.1	0.05	0.03	0.02							
500-1000	0.1	0.05	0.03	0.02							
1000-2000	0.1	0.05	0.03	0.02							
2000-5000	0.1	0.05	0.03	0.02							
5000-10000	0.1	0.05	0.03	0.02							
10000-20000	0.1	0.05	0.03	0.02							
20000-50000	0.1	0.05	0.03	0.02							
50000-100000	0.1	0.05	0.03	0.02							
100000-200000	0.1	0.05	0.03	0.02							
200000-500000	0.1	0.05	0.03	0.02							
500000-1000000	0.1	0.05	0.03	0.02							
1000000-2000000	0.1	0.05	0.03	0.02							
2000000-5000000	0.1	0.05	0.03	0.02							
5000000-10000000	0.1	0.05	0.03	0.02							
10000000-20000000	0.1	0.05	0.03	0.02							
20000000-50000000	0.1	0.05	0.03	0.02							
50000000-100000000	0.1	0.05	0.03	0.02							
100000000-200000000	0.1	0.05	0.03	0.02							
200000000-500000000	0.1	0.05	0.03	0.02							
500000000-1000000000	0.1	0.05	0.03	0.02							
1000000000-2000000000	0.1	0.05	0.03	0.02							
2000000000-5000000000	0.1	0.05	0.03	0.02							
5000000000-10000000000	0.1	0.05	0.03	0.02							
10000000000-20000000000	0.1	0.05	0.03	0.02							
20000000000-50000000000	0.1	0.05	0.03	0.02							
50000000000-100000000000	0.1	0.05	0.03	0.02							
100000000000-200000000000	0.1	0.05	0.03	0.02							
200000000000-500000000000	0.1	0.05	0.03	0.02							
500000000000-1000000000000	0.1	0.05	0.03	0.02							
1000000000000-2000000000000	0.1	0.05	0.03	0.02							
2000000000000-5000000000000	0.1	0.05	0.03	0.02							
5000000000000-10000000000000	0.1	0.05	0.03	0.02							
10000000000000-20000000000000	0.1	0.05	0.03	0.02							
20000000000000-50000000000000	0.1	0.05	0.03	0.02							
50000000000000-100000000000000	0.1	0.05	0.03	0.02							
100000000000000-200000000000000	0.1	0.05	0.03	0.02							
200000000000000-500000000000000	0.1	0.05	0.03	0.02							
500000000000000-1000000000000000	0.1	0.05	0.03	0.02							
1000000000000000-2000000000000000	0.1	0.05	0.03	0.02							
2000000000000000-5000000000000000	0.1	0.05	0.03	0.02							
5000000000000000-10000000000000000	0.1	0.05	0.03	0.02							
10000000000000000-20000000000000000	0.1	0.05	0.03	0.02							
20000000000000000-50000000000000000	0.1	0.05	0.03	0.02							
50000000000000000-100000000000000000	0.1	0.05	0.03	0.02							
100000000000000000-200000000000000000	0.1	0.05	0.03	0.02							
200000000000000000-500000000000000000	0.1	0.05	0.03	0.02							
500000000000000000-1000000000000000000	0.1	0.05	0.03	0.02							
1000000000000000000-2000000000000000000	0.1	0.05	0.03	0.02							
2000000000000000000-5000000000000000000	0.1	0.05	0.03	0.02							
5000000000000000000-10000000000000000000	0.1	0.05	0.03	0.02							
10000000000000000000-20000000000000000000	0.1	0.05	0.03	0.02							
20000000000000000000-50000000000000000000	0.1	0.05	0.03	0.02							
50000000000000000000-100000000000000000000	0.1	0.05	0.03	0.02							
100000000000000000000-200000000000000000000	0.1	0.05	0.03	0.02							
200000000000000000000-500000000000000000000	0.1	0.05	0.03	0.02							
500000000000000000000-1000000000000000000000	0.1	0.05	0.03	0.02							
1000000000000000000000-2000000000000000000000	0.1	0.05	0.03	0.02							
2000000000000000000000-5000000000000000000000	0.1	0.05	0.03	0.02							
5000000000000000000000-10000000000000000000000	0.1	0.05	0.03	0.02							
10000000000000000000000-20000000000000000000000	0.1	0.05	0.03	0.02							
20000000000000000000000-50000000000000000000000	0.1	0.05	0.03	0.02							
50000000000000000000000-100000000000000000000000	0.1	0.05	0.03	0.02							
100000000000000000000000-200000000000000000000000	0.1	0.05	0.03	0.02							
200000000000000000000000-500000000000000000000000	0.1	0.05	0.03	0.02							
500000000000000000000000-1000000000000000000000000	0.1	0.05	0.03	0.02							
1000000000000000000000000-2000000000000000000000000	0.1	0.05	0.03	0.02							
2000000000000000000000000-5000000000000000000000000	0.1	0.05	0.03	0.02							
5000000000000000000000000-10000000000000000000000000	0.1	0.05	0.03	0.02							
10000000000000000000000000-20000000000000000000000000	0.1	0.05	0.03	0.02							
20000000000000000000000000-50000000000000000000000000	0.1	0.05	0.03	0.02							
50000000000000000000000000-100000000000000000000000000	0.1	0.05	0.03	0.02							
100000000000000000000000000-200000000000000000000000000	0.1	0.05	0.03	0.02							
200000000000000000000000000-500000000000000000000000000	0.1	0.05	0.03	0.02							
500000000000000000000000000-1000000000000000000000000000	0.1	0.05	0.03	0.02							
1000000000000000000000000000-2000000000000000000000000000	0.1	0.05	0.03	0.02							
2000000000000000000000000000-5000000000000000000000000000	0.1	0.05	0.03	0.02							
5000000000000000000000000000-10000000000000000000000000000	0.1	0.05	0.03	0.02							
10000000000000000000000000000-200000000000000000000000000000	0.1	0.05	0.03	0.02							
20000000000000000000000000000-500000000000000000000000000000	0.1	0.05	0.03	0.02							
50000000000000000000000000000-1000000000000000000000000000000	0.1	0.05	0.03	0.02							
100000000000000000000000000000-2000000000000000000000000000000	0.1	0.05	0.03	0.02							
200000000000000000000000000000-5000000000000000000000000000000	0.1	0.05	0.03	0.02							
500000000000000000000000000000-10000000000000000000000000000000	0.1	0.05	0.03	0.02							
1000000000000000000000000000000-20000000000000000000000000000000	0.1	0.05	0.03	0.02							
2000000000000000000000000000000-50000000000000000000000000000000	0.1	0.05	0.03	0.02							
5000000000000000000000000000000-100000000000000000000000000000000	0.1	0.05	0.03	0.02							
10000000000000000000000000000000-200000000000000000000000000000000	0.1	0.05	0.03	0.02							
20000000000000000000000000000000-500000000000000000000000000000000	0.1	0.05	0.03	0.02							
50000000000000000000000000000000-1000000000000000000000000000000000	0.1	0.05	0.03	0.02							
100000000000000000000000000000000-2000000000000000000000000000000000	0.1	0.05	0.03	0.02							
200000000000000000000000000000000-5000000000000000000000000000000000	0.1	0.05	0.03	0.02							
500000000000000000000000000000000-10000000000000000000000000000000000	0.1	0.05	0.03	0.02							
1000000000000000000000000000000000-20000000000000000000000000000000000	0.1	0.05	0.03	0.02							
2000000000000000000000000000000000-50000000000000000000000000000000000	0.1	0.05	0.03	0.02							
5000000000000000000000000000000000-100000000000000000000000000000000000	0.1	0.05	0.03	0.02							
10000000000000000000000000000000000-200000000000000000000000000000000000	0.1	0.05	0.03	0.02							
20000000000000000000000000000000000-500000000000000000000000000000000000	0.1	0.05	0.03	0.02							
50000000000000000000000000000000000-1000000000000000000000000000000000000	0.1	0.05	0.03	0.02							
100000000000000000000000000000000000-2000000000000000000000000000000000000	0.1	0.05	0.03	0.02							
200000000000000000000000000000000000-5000000000000000000000000000000000000	0.1	0.05	0.03	0.02							
500000000000000000000000000000000000-10000000000000000000000000000000000000	0.1	0.05	0.03	0.02							
1000000000000000000000000000000000000-20000000000000000000000000000000000000	0.1	0.05	0.03	0.02							
2000000000000000000000000000000000000-50000000000000000000000000000000000000	0.1	0.05	0.03	0.02							
5000000000000000000000000000000000000-100000000000000000000000000000000000000	0.1	0.05	0.03	0.02							
100000000000000000000											