



Product: [GUMTE12](#) 

Universal tight buffered distribution cable LSZH jacket 12f MM OM4. CPR Dca.

Product Description

Universal (Indoor/Outdoor) tight buffered optical fiber distribution cable with Low Smoke Zero Halogen outer jacket. 12 fibers MM OM4. CPR Euroclass Dca.

Technical Specifications

Product Overview

Suitable Applications:	For outdoor and indoor use in structured (data) wiring systems such as industrial backbone, campus backbone, building backbone (riser) and/or horizontal cabling. For outdoor and indoor use in networks for industrial, telecom, cable TV and/or broadcast. Support all computer network applications such as FDDI, Gigabit Ethernet and ATM. Not suitable for blown installation.
------------------------	---

Fiber Specifications

Fiber Type:	OM4
Fiber Buffer Material:	LSZH - Low Smoke Zero Halogen (Flame Retardant)
Fiber Buffer Construction:	Tight
Fiber Buffer Diameter:	0.9 mm
Fiber Count:	12
Fiber Color Coding:	TIA coding (Gxxxxxx.T): Blue, Orange, Green, Brown, Gray, White, Red, Black, Yellow, Violet, Pink, Aqua

Cable Construction

Cable Core Water Blocking:	Waterblocking Glass Yarns
----------------------------	---------------------------

Outer Jacket Specifications

Jacket Material:	LSZH - Low Smoke Zero Halogen (Flame Retardant)
Nom. Diameter:	7.6 mm (0.30 in)

Optical Characteristics

Wavelength	850 nm	1300 nm
Max. Attenuation	2.9 dB/km	0.9 dB/km

Mechanical Characteristics

Mechanical Tests

Description	Tested Standard	Requirement/Value	According to Family Specification
Cable Min. Bend Radius Installation (Short Term)	IEC 60794-1-21-E6	152 mm	IEC 60794-2-20
Cable Min. Bend Radius Operation (Long Term)	IEC 60794-1-21-E11	76 mm	IEC 60794-2-20
Cable Max. Tensile Strength Installation (Short Term)	IEC 60794-1-21-E1	1500 N (340 lbf)	IEC 60794-2-20
Cable Max. Tensile Strength Operation (Long Term)	IEC 60794-1-21-E1	500 N (110 lbf)	
Cable Max. Crush Resistance Installation (Short Term)	IEC 60794-1-21-E3	5 kN/m	IEC 60794-2-20
Cable Max. Crush Resistance Operation (Long Term)	IEC 60794-1-21-E3	3 kN/m	IEC 60794-2-20

Bulk Cable Weight:	54 kg/km (36 lbs/1000ft)
--------------------	--------------------------

Temperature Range

Installation Temperature Range:	-5 °C to +50 °C
---------------------------------	-----------------

Operating Temperature Range:	-30 °C to +70 °C
Storage Temperature Range:	-30 °C to +70 °C

Standards and Compliance

Environmental Suitability:	Indoor/Outdoor - Euroclass Dca
Flammability / Reaction to Fire:	IEC 60332-1-2, IEC 60332-3-24
CPR Compliance:	CPR Euroclass: Dca-s1,d1,a1; CPR UKCA Class: Dca-s1,d1,a1
ISO/IEC Compliance:	IEC 60794ISO/IEC 11801-1
European Halogen Free Standards:	IEC 60754-1 - Halogen Amount = Zero, IEC 60754-2 - Halogen Acid Gas Amount - Max. Conductivity = 10 µS/mm, IEC 60754-2 - Halogen Acid Gas Amount - Min. pH = 4.3, IEC 61034-2 - Smoke Density Min. Transmittance = 60%
UK Regulation Compliance:	UKCA Mark

History

Update and Revision:	Revision Number: 0.246 Revision Date: 09-26-2025
----------------------	--

Part Numbers

Variants

Item #	Color	Putup Type	Length	EAN
GUMTE12.T62100	Blue	Reel	2,100 m	8719605222121
GUMTE12.TC2100	Pink	Reel	2,100 m	8719605222138
GUMTE12.TA2100	Turquoise	Reel	2,100 m	8719605220523
GUMTE12.022100	Violet, Erika	Reel	2,100 m	
GUMTE12.023100	Violet, Erika	Reel	3,100 m	8719605155016
GUMTE12.K22100	Violet, Erika	Reel	2,100 m	8719605159649
GUMTE12.TB2100	Violet, Erika	Reel	2,100 m	8719605220387

© 2026 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.