PRO SERIES

LITE SERIES

Wall Mount Racks

Reliable rack solutions for network, security and structured cabling applications.



6U | 9U | 12U | 15U
AVAILABLE SIZES

Temple Glass Perforated Door
DOOR OPTIONS

Standing • Wall Installation
FLEXIBLE DEPLOYMENT

Overview

QDB Pro Series Wall Mount Racks are built for professional network, security and structured cabling environments, delivering reliable construction, flexible installation and clean cable management.



- Reliable structure and all-welded frame contsruction.
- Standing and wall installation compatible.
- 19" standard installation.
- Removable side panels with optional side locks.
- Cable entry on both top cover and bottom panel.

Features

- Material: SPCC Cold Rolled Steel, All-Welded Frame Construction
- Thickness: 1.0 mm - 1.5 mm
- Surface Finish: Degreasing, Pickling, Phosphoric, Powder Coated.
- Loading Capacity : Frame Structure with the load of 60kg
- Degree of Protection : IP20
- Color : Black / Grey
- Front Tempered Glass Door c/w Lock
- Side Panel Lift-Off Type
- Cage Nut, 3 Way Power Distribution Unit



All-Welded Frame

Reliable structure and all-welded frame construction for long-term durability.



Flexible Installation

Standing and wall installation compatible to suit different environments.



Removable Side Panels

Removable side panels with optional side locks for easier maintenance.



Top & Bottom Cable Entry

Cable entry on both top cover and bottom panel for clean cable management.

Wall Mount Racks



PRO SERIES

Model	Size	D x W x H (mm)	Specifications	Door
QWM06U500-G	6U	540 x 500 x 320	1 Power Distribution Point – 3 ways	Temper Glass
QWM06U500-P	6U	540 x 500 x 320	1 Power Distribution Point – 3 ways	Perforated
QWM06U600-G	6U	540 x 600 x 320	1 Power Distribution Point – 3 ways	Temper Glass
QWM06U600-P	6U	540 x 600 x 320	1 Power Distribution Point – 3 ways	Perforated
QWM09U500-G	9U	540 x 500 x 435	1 Power Distribution Point – 3 ways	Temper Glass
QWM09U500-P	9U	540 x 500 x 435	1 Power Distribution Point – 3 ways	Perforated
QWM09U600-G	9U	540 x 600 x 435	1 Power Distribution Point – 3 ways	Temper Glass
QWM09U600-P	9U	540 x 600 x 435	1 Power Distribution Point – 3 ways	Perforated
QWM12U500-G	12U	540 x 500 x 570	1 Power Distribution Point – 3 ways	Temper Glass
QWM12U500-P	12U	540 x 500 x 570	1 Power Distribution Point – 3 ways	Perforated
QWM12U600-G	12U	540 x 600 x 570	1 Power Distribution Point – 3 ways	Temper Glass
QWM12U600-P	12U	540 x 600 x 570	1 Power Distribution Point – 3 ways	Perforated
QWM15U500-G	15U	540 x 500 x 715	1 Power Distribution Point – 3 ways	Temper Glass
QWM15U500-P	15U	540 x 500 x 715	1 Power Distribution Point – 3 ways	Perforated
QWM15U600-G	15U	540 x 600 x 715	1 Power Distribution Point – 3 ways	Temper Glass
QWM15U600-P	15U	540 x 600 x 715	1 Power Distribution Point – 3 ways	Perforated

LITE SERIES

Model	Size	D x W x H (mm)	Specifications	Door
QWL04U400-P	4U	530 x 400 x 240	1 x 3ways Power Distribution, 190mm Tray	Perforated
QWL04U500-P	4U	530 x 500 x 240	1 x 3ways Power Distribution, 290mm Tray	Perforated
QWL06U400-P	6U	530 x 400 x 330	1 x 3ways Power Distribution, 190mm Tray	Perforated
QWL06U500-P	6U	530 x 500 x 330	1 x 3ways Power Distribution, 290mm Tray	Perforated
QWL09U400-P	9U	530 x 400 x 460	1 x 3ways Power Distribution, 190mm Tray	Perforated