

# TK09

12VDC 5Amp Power Supply



<b>Input</b>	<b>Input voltage</b>	<b>AC 100-240V50/60Hz</b>
<b>Output</b>	<b>Output voltage</b>	<b>3-24V + / - 5%</b>
	<b>Power</b>	<b>60W</b>
	<b>Ripple wave</b>	<b>(mVp-p): &lt;1%</b>
	<b>Linear modulate</b>	<b>±0.5%max</b>
	<b>Temperature coefficient</b>	<b>±0.02%/℃</b>
	<b>Start time</b>	<b>&lt; 3s(240VAC output,1o=100%)</b>
	<b>Guard time</b>	<b>&gt;20ms(240VAC input,1o=100%)</b>
	<b>Output Standard</b>	<b>12V5A</b>
<b>Protection</b>	<b>Override protection</b>	<b>115%~200%kvA,automatic recovery</b>
	<b>Short-circuit protection</b>	<b>1 channel: automatic recovery</b>
<b>Insulation</b>	<b>Insulation strength</b>	<b>1500VAC/10mA,1MIN</b>
	<b>Insulation resistance</b>	<b>&gt;30MΩ, DC 500V</b>
<b>Environment</b>	<b>Working temperature</b>	<b>0℃~40℃,10%~90%RH</b>
	<b>Store temperature</b>	<b>-20℃~60℃,10%~90%RH</b>
<b>Size</b>	<b>Size/weight</b>	<b>160X100X43mm/450G</b>
	<b>Packing</b>	<b>50PCS</b>