

Key Features

16:9 Widescreen | The Power of HDMI | Optimized View Settings |

Enhanced Viewing Comfort



Product Description


The ViewSonic® VA1903h is a 19" (18.5" viewable) widescreen monitor that delivers value and performance for both home offices and small businesses. Equipped with HDMI input, a fast 5ms response time, and rich color performance, the VA1903h is great for a variety of applications ranging from viewing office documents to surfing the web. ViewSonic's exclusive ViewMode™ feature provides intuitive presets for optimized screen performance in different applications. In addition, Flicker-Free technology and a Blue Light Filter help to eliminate eye strain from extended viewing periods for improved productivity. An energy-saving Eco-mode reduces cost of ownership, making the VA1903h a great choice for both government and education.



19"
DISPLAY



TN
PANEL



1366 x 768
RESOLUTION

Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:

Display Size (in.):	19
Viewable Area (in.):	18.5
Panel Type:	TN
Resolution:	1366 x 768
Resolution Type:	WXGA (1280x800)
Static Contrast Ratio:	600:1
Dynamic Contrast Ratio:	50,000,000:1
Light Source:	LED
Brightness:	200 cd/m2
Colors:	16.7M
Color Space Support:	6 bit + 2 bit Hi FRC
Aspect Ratio:	16:9
Response Time (Typical GTG):	5ms
Viewing Angles:	90° horizontal, 65° vertical
Backlight Life (Hours):	30,000
Panel Surface:	Anti-glare, Hard coating (3H)

Compatibility:

PC Resolution (max):	1366 x 768
Mac® Resolution (max):	1366 x 768

Connector:

3.5mm Audio Out(1), VGA(1), HDMI 1.4 In(1)

Power:

Eco Mode (Conserve):	9.5W
Eco Mode (optimized):	12.5W
Consumption (typical):	15.3W
Consumption (max):	17W
Voltage:	AC 100-240V (universal), 50-60Hz
Stand-by:	0.5W
Power Supply:	Internal

Additional Hardware:

Kensington Lock Slot:	1
-----------------------	---

Controls:

Physical Controls:	Key Buttons 1, 2, 3, 4, 5 (Power)
On Screen Display:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)

Operating Conditions:

Temperature:	32-104° F (0 - 40° C)
Humidity (non-condensing):	20-90%

Mount:

VESA Compatible:	100 x 100 mm
------------------	--------------

Video Signal:

Frequency Horizontal:	15 ~ 82 KHz
Frequency Vertical:	50 ~ 75 Hz

Video Input:

Digital Sync:	TMD5
---------------	------

Ergonomics:

Tilt (Forward/Back):	3° / 18°
----------------------	----------

Weight (imperial):

Net (lbs):	4.6
Net Without Stand (lbs):	4.0
Gross (lbs):	6.6

Weight (metric):

Net (kg):	2.1
Net Without Stand (kg):	1.8
Gross (kg):	3.0

Dimensions (imperial) (WxHxD):

Packaging (in.):	19.8 x 13.7 x 4.1
Physical (in.):	17.2 x 13.5 x 6.7
Physical Without Stand (in.):	17.2 x 10.7 x 1.9

Dimensions (metric) (WxHxD):

Packaging (mm):	502.0 x 349.0 x 105.0
Physical (mm):	438.0 x 344.0 x 170.0
Physical Without Stand (mm):	438.0 x 271.0 x 48.0

General:

Regulations: cTUVus, FCC-B with ICES003, MX-CoC, Mexico Energy

PACKAGE CONTENTS: VA1903h Display, Power Cable, VGA Cable, Quick Start Guide

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

Warranty: Three-year limited warranty on parts, labor and backlight

UPC: 766907002270

Accessories:

LCD-DMA-001, LCD-DMA-002, LCD-WMK-001